



NOTE: MUST BE MOUNTED WITH CABLE EXITING THE BOTTOM OF LIGHT.

1. Install wall anchors that accept up to 1/4" threaded screws (not supplied), using the mounting dimensions noted on opposite side as reference, or use the light itself to mark positioning in preparation to fasten the guide lights onto the wall. Be sure to position the guide lights in plain view and just beyond the maximum allowable width of a standard trailer (8.5 feet).
2. Run and mount conduit (not provided) for power wires to a junction box (not provided) that will allow access for the cables of both guide lights.
3. Secure the guide lights to the wall using 1/4" thread stainless steel Wall Mounting Screws (not provided). LIGHTS MUST BE MOUNTED WITH CABLES EXITING THE BOTTOM (cables facing downwards).
4. Securely run cables to junction box, and use Waterproof Cord Connectors (Bell Connectors, Cable Glands) for cable entry into junction box.
5. Connect wires to power and close Junction Box. Guide lights can be connected in parallel. 12-24V lights are not polarity dependent, so wires can be connected either way (do not short circuit).

NOTE: Ensure that proper voltage is being supplied to the guide lights. Dimensions are provided for reference only, and due to slight manufacturing variances, it is recommended to use the light itself to mark positioning on the wall to ensure precision mounting.